

C 150 S | Flach-Bandschleifmaschine | Flat platen belt grinding machine

Die Baureihe C 150 S ist eine robuste Flachbandschleifmaschine für höchste Beanspruchung.

Eigenschaften

- ≡ Extrem robust und dadurch vibrationsarm
- ≡ Raumsparende Bauweise
- ≡ Schwenkbarer Schleiftisch
- ≡ 2 Bandgeschwindigkeiten
- ≡ Unterspannungsauslösung und Motorschutz
- ≡ Not-Stop-Einrichtung
- ≡ Schnellbandspannung
- ≡ Anschlussstutzen für Absaugung
- ≡ Absauganschluss auch in Tischvariante
- ≡ Auswechselbare Schleifplatte
- ≡ Anschlag- und Auflagetisch
- ≡ CE-Konform

The series C 150 S is a robust flat platen belt grinding machine for heavy duty operations.

Machine Characteristic

- ≡ *Robust and rigid design and therefore low in vibration*
- ≡ *Compact design*
- ≡ *Adjustable horizontal to vertical*
- ≡ *2 belt speed*
- ≡ *Low voltage trip and overload protection*
- ≡ *Emergency stop safety device*
- ≡ *Rapid belt tensioning and tracking*
- ≡ *Connection for dust extraction*
- ≡ *Connection to dust extraction also possible if used on work bench*
- ≡ *Replaceable grinding platen*
- ≡ *Stop and support table*
- ≡ *CE-conformity*

Technische Daten | Technical data

Bandabmessungen <i>Belt dimensions</i>	100 x 1.500 mm, 150 x 1.500 mm
Max. Schleiffläche <i>Max. grinding area</i>	150 x 500 mm
Bandgeschwindigkeit <i>Belt speed</i>	10 m/s, 20 m/s
Motorleistung <i>Motor rating</i>	1,1 / 1,4 kW
Spannung <i>Voltage</i>	400 V, 3/N/PE, 50 Hz
Betriebsart, Schutzart <i>Operation mode, protection class</i>	S1, IP 54
Absaugstutzen <i>Extraction pipe</i>	Ø 60 mm
Farbe <i>Colour</i>	Grau (RAL 7040), Blau (RAL 5017) Grey (RAL 7040), Blue (RAL 5017)
Gewicht Grundmaschine <i>Weight base machine</i>	70 kg

